

MSDS Document

Product Winter Products

1. Chemical Product and Company Identification

Product Winter Products

Synonyms: King De-Icing Salt, King Salt & Sand 50/50

MSDS ID 9001

Manufacturer

King Packaged Materials Company
3385 Harvester Road
Burlington, ON L7R 3Y5

Emergency Phone

(800) 461-0566

Revision Date 4/27/2010

2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Sodium Chloride	7647-14-5	50% - 100%			
Silica, total quartz	14808-60-7	50% - Max	0.05 mg/m ³	0.1 mg/m ³	

3. Hazard Identification

Emergency Overview

A single, short-term exposure to the dry powder presents little or no hazard.

Routes of Entry

Inhalation.
Ingestion.
Skin Absorption.

Eyes

Airborne dust may cause immediate or delayed irritation or inflammation.

Skin

May cause dry skin, discomfort, and irritation.

Inhalation - Acute

Exposure to airborne concentrations above exposure limits may cause irritation of the nose, throat and lungs.

Inhalation - Chronic

Risk of injury depends on duration and level of exposure.

Carcinogenicity

Suspect cancer hazard. Risk of cancer depends on duration and level of exposure.

Silicosis

This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica can cause silicosis, a seriously disabling and potentially fatal lung disease. See Section 4 for further information.

4. First Aid Information**Inhalation**

Move victim to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Skin Contact

Seek medical attention for rash, burns, irritation, dermatitis and prolonged unprotected exposures to wet cement, cement mixtures or liquids from wet cement.

Eye Contact

Rinse eyes thoroughly with water for at least 15 minutes, including under lids, to remove all particles. Seek medical attention for abrasions.

Additional Notes - Silicosis

There are three (3) types of silicosis:

1) Simple chronic silicosis - which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).

2) Accelerated silicosis - occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.

3) Acute silicosis - results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

5. Fire Fighting Measures

Flash Point

Not Available

FP Method Not Available

Extinguishing media

Media appropriate for surrounding fire.

6. Accidental Release Measures

Clean Up

Transfer to a closable, labelled salvage container for disposal by an appropriate method.

General

Avoid actions that cause the product to become airborne. Avoid inhalation of the product and contact with skin. Wear appropriate protective equipment as described in Section 8. Scrape wet product and place in container. Allow material to dry or solidify before disposal. Do not wash product down sewage and drainage systems or into bodies of water (e.g. streams).

Waste Disposal Method

Dispose of product according to Federal, State, Provincial and Local regulations.

7. Handling and Storage

Handling

Always use good industrial hygiene practices and safety guidelines. Stack bagged material in a secure manner to prevent falling.

Bagged product is heavy and poses risks such as sprains and strains to the back, the arms, the shoulders and the legs during lifting and mixing.

Minimize dust generation and accumulation.

Use with adequate ventilation.

Storage

Keep away from food and drinking water.

Store in a dry area.

Store material in its original container.

Keep containers tightly closed when not in use.

Protect from freezing

8. Exposure Controls and Personal Protection

Engineering controls

If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Skin Protection

Personal protective equipment for the body should be selected based on the task being performed. This includes gloves, coveralls and footwear.

Eye Protection

Approved safety eyewear should be worn, based on the risk assessments performed.

Respiratory Protection

Use of an approved respirator, based on a risk assessment is necessary. Respiratory protection should be selected based on the known or anticipated levels of exposure, and the work being performed.

Hand Protection

Approved gloves should be worn based on risk assessments.

Environmental Exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure their compliance with environmental protection legislation requirements. In some cases, it may be necessary to modify process equipment to reduce emissions to acceptable levels.

9. Physical and Chemical Properties

Physical State	Solid - Granular
Specific Gravity	2.5
Color/Appearance	White Crystalline S
Odor	Halogen Odor
pH	6.7 - 7.3
Boiling/Cond. Point	Not Available
Melting/Freezing Point	801 degrees Celsius
Solubility	26.4%
Evaporation Rate	Not Available
VOC %	Not Available
Percent Volatile	Not Available
Molecular Formula	Not Available
Viscosity	Not Available
Vapor Density	Not Available
Vapor Pressure	2.4

10. Stability and Reactivity**Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Materials to Avoid

None.

Conditions to Avoid

Store protected from unplanned moisture.

Stability

Stable under normal conditions.

Hazardous Polymerization

Will not occur

11. Toxicological Information**Environmental Effects**

There are no known significant effects or critical hazards.

12. Ecological Information

Environmental Effects

There are no known significant effects or critical hazards.

13. Disposal Considerations

Waste Disposal

Material should be disposed of in accordance with local, state and federal regulations. The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION for additional information on handling and employee protection.

14. Transportation Information

Transportation

This product is not classified as a Hazardous Material under U.S DOT or Canadian TDG regulations.

15. Regulatory Information

WHMIS

Hazardous Component(s) subject to WHMIS Ingredient Disclosure.
Class D2-A: Material causing other toxic effects.

16. Other Information

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, neither KPM Industries Ltd., nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.