

# **KING**

## **PermaSand - Grey**



### ***DESCRIPTION***

**PermaSand - Grey** is a quick setting polymer modified sand, designed specifically for filling joints of interlock pavers and slabs. Simply sweep over joints, mist with water and allow to harden. **PermaSand -Grey** provides a long-lasting flexible joint, resistant to erosion, weeds, and insects. It is ideal for residential and commercial uses: pool decks, patios, pedestrian walks, driveways, parking areas and roadways.

### ***DIRECTIONS***

#### ***NEW APPLICATIONS***

- 1) Ensure paver surface is dry prior to application.
- 2) Install and compact pavers.
- 3) Pour **PermaSand** onto surface and sweep over pavers, filling the joints. Compact again and repeat if necessary. (For best results use a vibrating plate compactor).
- 4) Sweep off excess **PermaSand** to just below the pavers surface.
- 5) Lightly mist with water 2-3 times at 5-10 minute intervals. Avoid excess water. Do not flood or generate water run-off.
- 6) Allow to dry at least 4 hours before opening to foot traffic.

#### ***EXISTING RENOVATIONS***

- 1) Remove existing jointing sand with a high-pressure water sprayer. Ensure all joints are cleared completely.
- 2) Refer to steps under New Applications.

### ***COVERAGE***

A 25kg bag covers approximately 50 to 100 sq. ft. (4.64m<sup>2</sup> to 9.29m<sup>2</sup>) depending on paver size, depth of joint and compaction.

**IMPORTANT: STORE IN DRY PLACE.  
USE ABOVE 0°C**

### ***GOOD to KNOW***

- ideal weather - above 50°F (10°C), dry with no rain forecast for next 24 hours
- narrow joints will be stronger & more durable
- joint width, high humidity or cold temperatures, may slow initial hardening
- maximum joint width:
  - PermaSand “Brown” up to 0.5" (1.3 cm)
  - PermaSand “Grey” up to 1" (2.6 cm)
- some maintenance may be required - particularly around pools

KING PACKAGED MATERIALS COMPANY warrants that this product is suitable for its' intended use. Surface conditions, applicator's skill and weather are beyond the manufacturer's control. Liability is limited to the replacement of defective material only. Proof of purchase is required.

***Mixing Strength With Satisfaction***

**KING PACKAGED MATERIALS COMPANY**  
P.O. BOX 699  
BURLINGTON, ONTARIO  
L7R 3Y5

**PHONE: 800-461-0566**  
**FAX: 905-333-3730**  
**E-MAIL: [consumer@kpmindustries.com](mailto:consumer@kpmindustries.com)**  
**WEBSITE: [www.king-products.com](http://www.king-products.com)**